

2nd March 2007

duroSET®/duroQIK®
Standard Specification for Underfloor Heating Applications

Product Specification

Surface preparation details for application to be followed as per product data sheets.

Priming

GP Primer applied at rate of 1lt/8m² to total floor surface.

Detailing and Reinforcement

Standard Elastofabric detailing.

Waterproofing Membrane (under heating element)

OPTION A duroSET®

OPTION B duroQIK®

Membrane applied as per Waterproofing Systems Specifications.

Heating Element Preparation

- 2mm Skim coat of 11Y Primer/duroMIX® or other self levelling compound to be applied as separation/protective layer between membrane and heating element
- Heating Element to be applied as per manufacturers recommendations
- 2mm Skim coat of 11Y Primer/duroMIX® or other self levelling compound to be applied as second separation/protective layer between heating element and tile adhesive
- Once the separation layer has been applied duroFIX® or duroBOND® tile adhesive to be used as per data sheet

Warranty

Waterproofing Systems Ltd will provide a producer statement and material warranty on receipt of the completed QC sheets with the warranty application.

Contact Details Waterproofing Systems Ltd

Technical Enquiries – John Stallard
Telephone +64 6 357 9148
Facsimile: +64 6 357 9410
Email: john@waterproofing.co.nz
Website: www.waterproofing.co.nz

The information contained herein is given in good faith as being true and accurate, but no liability is accepted by Waterproofing Systems Ltd, our employees, representatives or agents, for any loss or damage, direct or indirect, that may result from using the information or adopting recommendations and/or suggestions as actual conditions for use are beyond our control.

Important note: Waterproofing Systems Ltd recommends referral to all pertinent product data sheets listed in the above specification prior to commencing application.